

PE MOTION / 60 Sleeve Wrapping Machine

Dual axis continuous motion sealing system

Advantages:

- High speed automation with continuous-motion packaging system
- Two direction vertical & horizontal Servo motor driven cross seal
- Flexible and soft operation for vertical stacked package groups without slip out
- Without time loss for complete sealing sequence by vertical & linear motion operation
- Extreme precision and consistency with the sealing quality and package length positioning
- Easy integration to the production lines with adjustable in-feed conveyor
- The out put capacity can reach up to 50 packs/min. depending on the film, package dimension
- Low energy consumption
- More controls and cautions for more efficient production
- Advantage of easy and fast film roll change
- Instead of Pneumatic systems controlling weakness, servo motor gives more powerful solution about controlling pressure and quality sealing

Features:

- Two direction vertical & horizontal Servo motor driven cross seal,
- Seal bar length 640mm
- Maximum cross seal height 200mm
- Maximum film width: 700mm
- Linear speed of the conveyors: 20 mt / min
- The latest Siemens or Delta environment for all intelligent controls
- Touch panel with different languages and easy graphic controls for operator
- Installed power: 400V. 3 phase, 6kW, 9 Amps.
- Encoder controlled length adjustment for automatic synchronization with the speed
- Low film consumption
- Advantage of film tension release on the cross-sealing point
- Automatic package length scanning
- Height adjustable cross sealer (Optional motorized control)
- Control of optional integrated external conveyor from operator panel.
- Consistency in packaging quality
- Integrated automatic external in-feed belt control option
- Easy change over between different product sizes and speed changes
- Recipe application with different package dimensions
- Automatic film dispenser with tension control
- Complete closed housing with limit switch controlled windows for security
- Photocell controlled package in-feed
- ISO 9001 quality standard with the relevant norm's confirmations,
- Festo Pneumatics, Moeller, Siemens electric components
- CE marking,
- Manufacturer's guarantee for spare part stock and after sales support,
- One year warranty on non-wearable parts
- Color: Metallic dark gray (RAL code: custom color)



PE MOTION / 60 Sleeve Wrapping Machine

Dual axis continuous motion sealing system

Advantages:

- High speed automation with continuous-motion packaging system
- Two direction vertical & horizontal Servo motor driven cross seal
- Flexible and soft operation for vertical stacked package groups without slip out
- Without time loss for complete sealing sequence by vertical & linear motion operation
- Extreme precision and consistency with the sealing quality and package length positioning
- Easy integration to the production lines with adjustable in-feed conveyor
- The out put capacity can reach up to 50 packs/min. depending on the film, package dimension
- Low energy consumption
- More controls and cautions for more efficient production
- Advantage of easy and fast film roll change
- Instead of Pneumatic systems controlling weakness, servo motor gives more powerful solution about controlling pressure and quality sealing

Features:

- Two direction vertical & horizontal Servo motor driven cross seal,
- Seal bar length 640mm
- Maximum cross seal height 200mm
- Maximum film width: 700mm
- Linear speed of the conveyors: 20 mt / min
- The latest Siemens or Delta environment for all intelligent controls
- Touch panel with different languages and easy graphic controls for operator
- Installed power: 400V. 3 phase, 6kW, 9 Amps.
- Encoder controlled length adjustment for automatic synchronization with the speed
- Low film consumption
- Advantage of film tension release on the cross-sealing point
- Automatic package length scanning
- Height adjustable cross sealer (Optional motorized control)
- Control of optional integrated external conveyor from operator panel.
- Consistency in packaging quality
- Integrated automatic external in-feed belt control option
- Easy change over between different product sizes and speed changes
- Recipe application with different package dimensions
- Automatic film dispenser with tension control
- Complete closed housing with limit switch controlled windows for security
- Photocell controlled package in-feed
- ISO 9001 quality standard with the relevant norm's confirmations,
- Festo Pneumatics, Moeller, Siemens electric components
- CE marking,
- Manufacturer's guarantee for spare part stock and after sales support,
- One year warranty on non-wearable parts
- Color: Metallic dark gray (RAL code: custom color)

